

WEB BOARDS, LLC



33 FISHERVILLE ROAD, CONCORD N.H. 03303

TEL: 603-228-6617 FAX: 603-228-6545

Thank you for choosing Web Boards, LLC.

We appreciate your business!

www.web-boards.net

F3 - Installation Instructions

OR

ST - Model [w/pegs] Only

F3 and/or ST Web Boards® / BRAKE PEDAL ADJUSTMENTS**

-  Unbolt and remove both foot peg pads (riders), in addition to the black steel plugs under the riders' pegs.
-  Place the vinyl peg spacer provided onto the top of the peg. (You will install your Web Board on top of this spacer)
-  Set the WEB BOARDS ® on the rider's pegs. (Make sure the vinyl spacer that is provided has been inserted between the Web Board and the peg).
-  Align the holes on the on the riders pegs with those in the center of the spacers as well as your WEB BOARDS ®, and securely bolt in place using the ¼-20 s/s 3/16 x 1-1/2" bolts, with Nylok nuts.
-  **** If you are installing a Web Boards® Brake Pedal, Unscrew and remove the rubber pad from the top of the brake pedal, once you have done this; line the metal spacer plate up with the holes on top of the factory brake. ****
-  **** Insert the fixed studs of the Web Boards® brake pedal thru the factory pedal. Fasten your new pedal from underneath with the washers and the locknuts provided. ****

We recommend that you periodically check all nuts and bolts, to ensure they are tightened securely

HARDWARE INCLUDED

⑧ 2 - Vinyl peg Spacers

⑧ 4 ea - ¼ -20 s/s 3/16 Flat Head socket cap bolts x 1-1/2" long with washers, and Nylok nuts.

(Used to install WEB BOARDS® to riders pegs)

**** If you have a Web Boards® Brake Pedal ****

1 - Brake Pedal

1 - S/S spacer plate

2 ea - washers/nylok nuts

**** We recommend that you periodically check all nuts and bolts, to ensure they are tightened securely****